



VE412PN

**Enclosure,vector,surface mounted,IP65,48M,UV stable,with metric cable entry**

## Technical properties

### Architecture

Fixing mode	surface-mounting
-------------	------------------

### Functions

With a pipe-in lead	Yes
---------------------	-----

### Configuration

Number of modules	48
-------------------	----

### Compatibility

Suitable for Multimedia	No
-------------------------	----

### Voltage

Rated operational voltage in DC	1000 V DC
---------------------------------	-----------

### Electric current

Rated current	63 A
---------------	------

### Dimensions

Depth of installed product	151 mm
Internal depth	151 mm
Height of installed product	677 mm
Width of installed product	310 mm
Width in division units	12
Thickness of sidewall material	2.5 mm

### Cover, door

Type of door closing	Latch
Identification od protection index	65
Interlockable	No
Number of keylock of the door	0
Cover type	Closed (plain)
Door locking	without
Door leave	single
Transparent cover or door	Yes

### Materials

Colour	light grey
Colour	light grey

### Installation, mounting

Suitable for outdoor use

Yes

#### Connection

Number of conduit inlets	12
--------------------------	----

#### Settings

Enclosure type	Distributor empty cabinet
----------------	---------------------------

#### Equipment

Number of rows	4
----------------	---

Quantity of section in width	1
------------------------------	---

Quantity of rails	4
-------------------	---

Can be accessorized	Yes
---------------------	-----

Number of openings for flange plates	46
--------------------------------------	----

Extension possible	No
--------------------	----

Earthing terminal block	No
-------------------------	----

Neutral terminal block	No
------------------------	----

Signal passing door	Yes
---------------------	-----

#### Safety

REACH conform	No
---------------	----

RoHS conform	Yes
--------------	-----

#### Use conditions

Operating temperature	-25...40 °C
-----------------------	-------------