



## Small distributor,golf,flush,MM,2row,36M,white door, slotted

## **Technical properties**

| With a pipe-in lead                | Yes                      |
|------------------------------------|--------------------------|
| Configuration                      |                          |
| Number of modules                  | 36                       |
|                                    |                          |
| Electric current                   |                          |
| Rated current                      | 63 A                     |
| Dimensions                         |                          |
| Insertion depth                    | 72 mm                    |
| Depth of wall niche                | 72 mm                    |
| Depth of installed product         | 97.5 mm                  |
| Internal depth                     | 97.5 mm                  |
| Height of installed product        | 418 mm                   |
| Installation height                | 382 mm                   |
| Width of installed product         | 460 mm                   |
| Built-in width                     | 426 mm                   |
| Cover, door                        |                          |
| Type of door closing               | Latch                    |
| Identification od protection index | 40                       |
| Interlockable                      | No                       |
| Number of keylock of the door      | (                        |
| Door locking                       | withou                   |
| Door leave                         | single                   |
| Transparent cover or door          | No                       |
| Materials                          |                          |
| Colour                             | pure white               |
| Installation, mounting             |                          |
| Suitable for outdoor use           | No                       |
| Settings                           |                          |
| Enclosure type                     | Distributor empty cabine |
| Equipment                          |                          |
| Number of units                    | 18                       |
| Number of rows                     | 2                        |
| Quantity of section in width       | 1                        |

VF218PZF

Subject to technical modifications

| Quantity of rails                    | 2   |
|--------------------------------------|-----|
| Can be accessorized                  | Yes |
| Number of openings for flange plates | 0   |
| Extension possible                   | Yes |
| Earthing terminal block              | No  |
| Neutral terminal block               | No  |
| Signal passing door                  | Yes |

GWT Glow wire test

## Safety

REACH conform

No

650 °C