



VS418PZF

**Small distributor,golf,surface,MM,4row,72M,white door, slotted**

## Technical properties

### Architecture

Fixing mode	surface-mounting
-------------	------------------

### Functions

With a pipe-in lead	Yes
---------------------	-----

### Configuration

Number of modules	72
-------------------	----

### Electric current

Rated current	63 A
---------------	------

### Dimensions

Depth of wall niche	72 mm
---------------------	-------

Depth of installed product	99 mm
----------------------------	-------

Internal depth	99 mm
----------------	-------

Height of installed product	647 mm
-----------------------------	--------

Width of installed product	390 mm
----------------------------	--------

### Cover, door

Type of door closing	Latch
----------------------	-------

Identification od protection index	40
------------------------------------	----

Interlockable	No
---------------	----

Number of keylock of the door	0
-------------------------------	---

Door locking	without
--------------	---------

Door leave	single
------------	--------

Transparent cover or door	No
---------------------------	----

### Materials

Colour	pure white
--------	------------

### Installation, mounting

Suitable for outdoor use	No
--------------------------	----

### Settings

Enclosure type	Distributor empty cabinet
----------------	---------------------------

### Equipment

Number of units	18
-----------------	----

Number of rows	4
----------------	---

Quantity of rails	4
-------------------	---

Can be accessorized	Yes
Number of openings for flange plates	0
Extension possible	Yes
Earthing terminal block	No
Neutral terminal block	No
Signal passing door	Yes

#### Standards

GWT Glow wire test	650 °C
--------------------	--------

#### Safety

REACH conform	No
---------------	----