

Date tehnice pentru produs: WSAIE4040R

Cadru modular 2 rânduri a câte 17M, pentru Î=400 L=400mm

pe balamale, cu șine DIN, compatibil cu WSA4040210



SCHRACK-Info

- For installation of modular devices on DIN-rails
- The distance between the DIN-rails (centre-centre) is 140mm
- The usable depth between the front cover of the WSAIE modular chassis and the WSA enclosure door is 82.5mm
- Material thickness: 1.2mm
- Degree of protection: IP3XD according to IEC 60529
- Color: RAL 7035 (Light grey)
- Supply includes:
 - 1 Piece of front door with 45mm cutouts
 - 2 Pieces of vertical profiles
 - 2 Pieces of closures (top/bottom)
 - DIN-rails
 - Mounting material


Fișe tehnice

Lățime netă (mm)	400,00
Înălțime (mm)	400,00
Adâncime netă (mm)	61,00

Fișe tehnice - Continuare

Masă netă (kg.)	3,30
Culoare	Gri deschis
Accesorii opționale	WSAIE00BL-

Desen dimensional: Cadru modular 2 rânduri a câte 17M, pentru Î=400 L=400mm



Tabel articole

Descriere	Cod comandă
Cadru modular 2 rânduri a câte 17M, pentru $\hat{I}=400$ L=400mm pe balamale, cu șine DIN, compatibil cu WSA4040210	WSAIE4040R
Accesorii opționale	
Plastic quarter turn lock for WSAIExxxxR	WSAIE00BL